

FORGED PISTON for RB26DETT



2 more size options are now available!

TOMEI's answer to cover those market demands both for the rebuild needs with 86.2mm bore, as well as competition needs by 87.5mm bore.

Ellipse and barrel-shaped design basing on precise analysis to achieve the best piston profile at metal-expanded condition under operating temperature range.

This design of TOMEI original helps to keep the best alignment against the piston cylinders that reduces friction loss, blow-by gas, as well as unwanted mechanical noise.

	Bore	Reces	P/N	Disp l acement	Pin Dia.	Comp.Height	Piston Crown Volume	Top ring	Second ring	Oil ring
New options	Ф86.2	0	1121862112	RB26/2579cc	- Φ21	30.00mm	-11.2cc	1.20 × 3.10mm	1.20 × 3.90mm	2.5 × 3.10mm
		×	1121862111	RB28/2719cc			-13.0cc			
	Ф86.5	0	1121865112	RB26/2597cc			-11.2cc			
		×	1121865111	RB28/2738cc			-13.0cc			
	Ф87.0	0	1121870112	RB26/2628cc			-11.2cc			
		×	1121870111	RB28/2770cc			-13.0cc			
options	Ф87.5	0	1121875112	RB26/2658cc			-11.2cc			
		×	1121875111	RB28/2802cc			-13.0cc			

with VALVE RECESSION

JPY 168,000

without VALVE RECESSION

JPY 158.000

RELATED PRODUCT

NISSAN RB28 KIT

Super quick response from the optimized weight balance and wide range [With Conrod Bearings Bundle Pack] of torquey output from the extra displacement.

The RB28 kit is now available with the new 86.2 / 87.5mm pistons.

Tomel has made an option to include their Competition Bearing Series product with our kits. All the engine internals are brought to static temperature (20 degrees Celsius) and blueprinted with 0.040-0.060mm dearance bearings. This eliminates the measuring and blueprinting process for the customer, so the kit can be installed with less hassle.

-114	HAMI
000	

Bore	Reces	P/N	JPY	
Φ86.2	0	252012		
Ψ80.2	×	252010	580.000	
Φ86.5	0	221028		
Ψ80.5	×	221022		
Ф87.0	0	221029	000,000	
Ψ87.0	×	221023		
Φ87.5	0	252013		
Ψ67.3	×	252011		

Во	re	Reces	P/N	JPY		
Φ86	:)	0	250024			
Ψοι	J. Z	×	250022			
Φ86.5		0	250013			
Ψοι	5.5	×	250001	610.000		
Φ87	7 0	0	250014	,		
Ψο		×	250002			
Φ87	7 5	0	250025			
Ψ67.3		×	250023			

TOMEI POWERED INC.